

Feel greater power of DNB Breaker Series!
Free to choose DNB Breaker series as per work site & working condition

You can find different performance of DNB Breaker manufactured by DNHI Co., Ltd.

The advantage of DNB Breaker

1. Steady powerful impact
2. Long durability realized by semi-permanent nitrogen charging system
3. Easy maintenance of accumulator without disassembly
4. Convenient installation to all kinds of excavators



D10 II s D20 II s D25 II s D30 II s D40 II s D55 II s D60 II s D65 II s D70 II s D90 II s D110 II s D130 II s D160 II s D200 II s D300 II s D500 II s

DNB

Hydraulic Breaker
 Dynamic D500 II s

Powerful

- Certified outstanding power
- Consistent impact power
- Highest productivity

Efficient

- Simple and easy maintenance
- Convenient installation on all kinds of excavators

Durable

- Excellent durability
- Energy efficient
- Low vibration, low noise

Reliable

- Fast delivery of replacement parts
- Reliable A/S backup system
- Low A/S rate



Main Specifications

ITEM/MODEL		D10 II s	D20 II s	D25 II s	D30 II s	D40 II s	D55 II s	D60 II s	D65 II s	D70 II s	D90 II s	D110 II s	D130 II s	D160 II s	D200 II s	D300 II s	D500 II s
OPERATING WEIGHT	kg	75	100	200	300	520	855	1050	1350	1660	1860	2250	2600	3300	3800	6500	12900
IMPACT RATE	BPM	900~1200	900~1200	550~1100	500~1000	400~700	350~550	350~500	350~500	350~500	350~500	360~520	320~420	300~400	250~350	250~350	200~300
IMPACT ENERGY	J	300	300	580	1000	1400	2000	2200	3700	4300	4400	5800	6920	9100	10500	12500	19500
OPERATING OIL FLOW	LPM	15~20	15~25	25~50	45~80	60~90	80~110	70~110	80~130	120~160	120~160	160~230	170~240	190~250	220~350	250~400	300~450
OPERATING PRESSURE	bar	100~120	100~120	120~140	120~140	135~150	140~160	140±5	140±5	140±5	140±5	140±5	145±5	155±5	155±5	160±5	160~180
CARRIER WEIGHT	ton	0.5~1.3	0.8~3	1.3~5	3.5~8	6~12	13~20	16~20	16~25	18~30	18~30	25~40	30~55	40~60	45~80	60~90	80~140
TOOL DIAMETER	mm	38	45	60	75	90	100	115	120	130	130	140	155	170	180	195	235